

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 1 028 589 A1**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:

16.08.2000 Bulletin 2000/33

(51) Int. Cl.7: **H04N 5/445**

(21) Application number: 00100857.2

(22) Date of filing: 18.01.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 12.02.1999 GB 9903220

(71) Applicant:

Pace Micro Technology PLC  
Saltale, Shipley, BD14 3LF (GB)

(72) Inventor: Entwistle, Paul

Oxenhope, West Yorkshire (GB)

(74) Representative:

Wood, Graham et al  
Balley Walsh & Co,  
5 York Place  
Leeds LS1 2SD (GB)

**(54) Improvements relating to television guide systems**

(57) The invention relates to the generation of an Electronic Programme Guide (EPG) from data transmitted to a receiver location. The EPG is generated from the data for display on a screen. The receiver of the data for the programmes to be displayed and to which the EPG relates is capable of interrupting the display of the programmes and saving the data in a memory for subsequent display at a later time. The present invention ensures that the EPG data is adjusted in accordance with the data held in the memory so as to continue to be synchronised with the programmes which can be displayed.

**EP 1 028 589 A1**

## Description

[0001] The invention to which this invention relates is to the generation and control of an electronic programme guide (EPG) of the type which is generated on a television display screen and transmitted and received from a remote broadcast location.

[0002] An EPG and data relating to the same is typically transmitted at regular intervals or continuously to allow the guide to be generated and displayed and/or updated as required. The EPG is an increasingly important requirement in television broadcasting systems as the number of channels which can be received increases. The EPG systems are frequently improved as the guide or the broadcast systems upon which the same are carried are improved and progressed and usually include a series of bars and columns in a grid format which includes a series of cells, each of the cells indicating a particular programme, typically including an indication of the title, and each of the cells is positioned with respect to a time indication and a channel indication so as to provide to the user and indication of where and when they can view various programmes.

[0003] One problem is the increased ability to control the display of programmes at the viewer location to suit the viewer's wishes. This means that if, for example, the viewer is watching a programme and wishes to interrupt the programme but not miss the remainder of the programme they can decide to store in the local memory of the apparatus the remainder of the programme, and then recommence viewing of the stored programme at the desired time. This feature may be of particular importance in the future and the problem with this is that the delaying of the transmission of the programme at a location means that the display of the programme at that location and subsequent programmes are then out of synchronisation with the EPG data and information which is transmitted to that location. This can be confusing and/or irritating to the viewer.

[0004] The aim of the present invention is to provide a system whereby the localised delaying or altering of the viewing of a programme is taken into account in the generation of the electronic programme guide at that location or locations.

[0005] In a first aspect of the invention there is provided television data receiving apparatus which allows the display of a series of programmes at at least one location from data received, means for receiving data relating to and for generating an electronic programme guide at said location, which guide indicates the schedule of programmes and other information which can be displayed via the apparatus and means whereby the display of a programme or programmes can be delayed and or interrupted and data received for the remaining programme and/or subsequent programmes stored in a memory means for selective display at a later time and characterised in that the electronic programme guide at that location is adjusted in response to the delay in dis-

play of the remainder of the programme and/or subsequent programmes so as to provide synchronisation of the adjusted electronic programme guide details with the display of the remainder of the programme and/or subsequent programmes.

[0006] Thus, according to the invention, the schedule of the electronic programme guide is linked to the use of the local memory in the apparatus so as to automatically reflect scheduling adjustments caused by the time shifting of broadcast programmes by the user of the apparatus at a specific location rather than the broadcaster of the data. The inclusion of programme delay means and memory in set top boxes provides the ability to pause a broadcast programme and continue watching the same later to be possible and this has given rise to the problem of displaying the start and end times of the programme in an EPG accurately as the start and end times are adjusted in response to the local viewer operation of the storage device instead of the original transmission schedule.

[0007] By providing for the automatic and interactive modification and presentation of the EPG schedule at specific locations so as to represent the time shifting which may occur in the display of the remainder of a programme or subsequent programmes, so the EPG can be kept in synchronisation with the viewing schedule at that users location and display to the user the correct start and end times. This allows the user to organise their viewing knowing when time displaced broadcast programme and subsequent programmes will finish. Furthermore, they can schedule to watch, for example, a particular programme whilst pausing another which they were previously watching and then restarting the original programme and the EPG will adjust accordingly. The method of automatic temporal shifting within the EPG allows the selection to be made by locally processing and adjusting the broadcast schedule.

[0008] In one embodiment the electronic programme guide generating means receives a first signal to indicate the commencement of a delay in broadcast of programme data and commencement of storage of the same in the memory and a second signal to indicate when the viewing of the said data recommences and adjusts the electronic programme guide to take into account the time period between said first and second signals. Typically, the said signals or additional signals are received by the means for generating the electronic programme guide and indicate the particular programme and channel which has been selectively delayed by the user, so as to allow the EPG to be adjusted accordingly with respect to the appropriate channel and programme.

[0009] Typically the electronic programme guide is adjusted by generating an additional display feature which indicates the actual viewing schedule of the user, including any delays in viewing of programmes. In one embodiment the electronic programme guide is dis-

played as a grid with a number of rows, each indicating a channel and located with respect to a time band, and if a selected delay of a programme is made by the user an additional row is generated on the electronic programme guide to indicate the real time viewing schedule for the user at that apparatus location and including the delay.

[0010] In a further aspect of the invention there is provided television programme data receiving apparatus which allows the display of a series of programmes at at least one location from data received, means for receiving data relating to and for generating an electronic programme guide at said location, which guide indicates the schedule of programmes and other information which can be displayed via the apparatus and means whereby the display of a programme or programmes can be selectively delayed and or interrupted by the user of the apparatus at the location and data which is then received for the remaining programme and/or subsequent programmes which have been delayed stored in a memory means for selective display on the apparatus at a later time and characterised in that the electronic programme guide at that location is adjusted in response to the localised delay in display of the remainder of the programme and/or subsequent programmes so as to synchronise the adjusted electronic programme guide details to take into account the delay in display of programme material.

[0011] Specific embodiments of the invention will now be described with reference to the accompanying diagrams wherein:-

Figure 1 indicates a typical EPG schedule;

Figure 2 indicates the schedule of Figure 1 with highlighted viewing choices;

Figure 3 illustrates the adjustments to the EPG made in one embodiment of the invention;

Figure 4 illustrates an alternative embodiment of an EPG according to the invention; and

Figure 5 illustrates a yet further embodiment of the invention.

[0012] It is possible for a user to record or store data onto a memory means such as a hard disc drive, (HDD), provided in or connected with data receiving apparatus at their premises. The data can relate to a particular programme or programmes on a particular channel or the like whilst it is being viewed. This allows the viewer to pause and then recommence watching that channel by locally storing the broadcast channel data which is received during the pause or delay in viewing. When the user selects to continue viewing the programme is generated from the data which is stored in the HDD and recommences at the point in the programme where the

pause occurred and is then viewed by the viewer. The writing of programme material which has been transmitted and received in that time is contained and stored in a time buffer. The buffer therefore represents time shifted programme material such as an entire broadcast channel or potentially multiplex channels and in accordance with the invention the EPG which is generated reflects the fact that the programme material associated with a channel needs to be locally offset by the time buffer so that the EPG reflects the schedule for that particular user which has been changed due to the selection of the delay function and therefore differs from the EPG schedule which would be generated from the data transmitted to all user locations by the broadcaster.

[0013] In accordance with the invention the EPG generation means can identify the time delay from data signal received from the memory means and can also identify the location in terms of channel and programme of the data which has been stored during the delay. One possibility is to represent this by "slipping" the row of the EPG display which relates to the channel which has been delayed and the extent of this "slippage" is determined by the buffer quantity i.e. the length of the delay. A further enhancement can be to display the original channel row timings as that is still accessible to be viewed immediately by the viewer and the data for this is still received from the broadcaster, and generate an additional channel which reflects the contents of the HDD or memory means so as to illustrate to the viewer the extent of delay and allow the viewer to select which source to watch. A yet further embodiment is to represent the duration of programmes as rectangular areas and to illustrate displacement through use of the delay facility by diagonal lines which highlight the skew between the broadcast and the stored schedules at the particular location. A yet further embodiment is to only show the time displacement of an individual programme on that channel rather than the whole channel so that for example if a film is paused to watch the news, the EPG displays the skewed end time of the film only and allows further viewing planning to be undertaken.

[0014] Figure 1 illustrates one example and illustrates a typical EPG schedule for 3 channels, namely Ch1, Ch2 and Ch3 and shows the schedule of programmes from 7 o'clock to 9 o'clock. Normally, the user or viewer of the EPG will highlight the viewing choices, as shown in Figure 2, so that, for example, between 7 and 7.30 they are watching channel 1, then between 7.30 and 8.30 channel 2 and wish to watch the news at 8.00 and music at 9.00 on channel 3. It will be seen however that these selections overlap but by using the storage system of the apparatus the film on channel 2 can be interrupted and delayed by the user so that the news on channel 3 can be watched at the appropriate time as shown in figure 3. The viewing of the film is continued with the display generated from the data held on the memory means at the data receiver at the user location so that the end of the film can be watched. However

due to the delay the users viewing schedule is then out of synchronisation with the schedule of figure 2, so that the film in fact ends at 9 o'clock in reality as shown in Figure 3 as opposed to 8.30 shown in Figure 2. Thus, with Figure 3, the EPG schedule is locally reprocessed to reflect the new viewing times, i.e. the film is delayed from starting until the selection on channel 1 is complete and thus the start of the film is stored in the local memory. When the film is started from the memory then the viewing of that is interrupted by the insertion of the news from Channel 3 which is shown live and the remainder of the film is paused until the news has finished and viewing then recommences.

[0015] An alternative method of displaying the process schedule data is shown in Figure 4 which shows a "slipped" channel representation which represents the data which is being stored on the HDD memory. Thus, it is shown that in Channel 1 the term "Some TV" is being watched and a film has started on Channel 2 while Channel 1 was being watched but the new line "HDD" indicates when the actual film started as it was previously being stored in the HDD memory means and so represents to the viewer the change in schedule.

[0016] A yet further alternative arrangement is shown in Figure 5 wherein a static selected viewing channel can be displayed that always remains visible even when the channels are scrolled down so that in figure 5 it is shown that the top line indicates the highlighted viewing which is "some TV" followed by "film" followed by "news" followed by "film" and then music while the remainder of the schedule indicates to the viewer what changes have occurred in the EPG schedule as a result of the viewing which has taken place.

#### Claims

1. Television data receiving apparatus which allows the display of a series of programmes at at least one location from data received, means for receiving data relating to and for generating an electronic programme guide at said location, which guide indicates the schedule of programmes and other information which can be displayed via the apparatus and means whereby the display of a programme or programmes can be delayed and or interrupted and data received for the remaining programme and/or subsequent programmes stored in a memory means for selective display at a later time and characterised in that the electronic programme guide at that location is adjusted in response to the delay in display of the remainder of the programme and/or subsequent programmes so as to provide synchronisation of the adjusted electronic programme guide details with the display of the remainder of the programme and/or subsequent programmes.
2. Television data receiving apparatus according to claim 1 characterised in that the schedule gener-

ated for the electronic programme guide is linked to the use of the local memory at the location and display so as to automatically reflect scheduling adjustments caused by the time shifting of broadcast programmes by the user selecting to delay the display of a programme.

3. Television data receiving apparatus according to claim 1 characterised in that the electronic programme guide generating means receives a first signal to indicate the commencement of a delay in broadcast of programme data and commencement of storage of the same in the memory and a second signal to indicate when the viewing of the said data recommences and adjusts the electronic programme guide to take into account the time period between said first and second signals.
4. Television data receiving apparatus according to claim 3 characterised in that the said signal or additional signals are received by the means for generating the electronic programme guide and indicate the particular programme and channel which has been selectively delayed by the user.
5. Television data receiving apparatus according to claim 1 characterised in that the electronic programme guide is adjusted by generating an additional display feature which indicates the actual viewing schedule of the user, including any delays in viewing of programmes.
6. Television data receiving apparatus according to claim 5 wherein the electronic programme guide is displayed as a grid with a number of rows, each indicating a channel and located with respect to a time band, and if a selected delay of a programme is made by the user an additional row is generated on the electronic programme guide to indicate the real time viewing schedule for the user at that apparatus location and including the delay.
7. Television programme data receiving apparatus which allows the display of a series of programmes at at least one location from data received, means for receiving data relating to and for generating an electronic programme guide at said location, which guide indicates the schedule of programmes and other information which can be displayed via the apparatus and means whereby the display of a programme or programmes can be selectively delayed and or interrupted by the user of the apparatus at the location and data which is then received for the remaining programme and/or subsequent programmes which have been delayed stored in a memory means for selective display on the apparatus at a later time and characterised in that the electronic programme guide at that location is adjusted

in response to the localised delay in display of the remainder of the programme and/or subsequent programmes so as to synchronise the adjusted electronic programme guide details to take into account the delay in display of programme material. 5

10

15

20

25

30

35

40

45

50

55

5

Figure 1

7.00		7.30		8.00		8.30		9.00		
Ch1	Some TV		Next programme ...					Even more ..		
Ch2	.....		Film starts .....					.....		
Ch3	Soap ...			News		Even more soap ....			Music	

	7.00	7.30	8.00	8.30	9.00
Ch1	Some TV		Next programme ...		Even more ..
Ch2	.....	Film starts			.....
Ch3	Soap ...		News	Even more soap ....	Music

Figure 2

Figure 3

	7.00	7.30	8.00	8.30	9.00
Ch1	Some TV		Next programme ...		Even more ..
Ch2	.....	Film	Film continues		
Ch3	Soap ...		News	Even more soap ....	Music

	7.00	7.30	8.00	8.30	9.00
Ch1	Soap TV	Next programme ...			Even more ..
Ch2	.....	Film starts .....			.....
hdd	.....	Film starts .....			....
Ch3	Soap ...		News	Even more soap ....	

Figure 4

	Soap TV	Film	News	Film continues	Music
	7.00	7.30	8.00	8.30	9.00
Ch1	Soap TV	Next programme ...			Even more ..
Ch2	.....	Film	Film continues		
Ch3	Soap ...		News	Even more soap ....	Music
Ch44	Old TV ...		Special interest ....		Hobby TV ...
Ch45	News	Sports ....			
Ch46	Other sports .....				More sport ..

Figure 5



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 10 0857

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	EP 0 836 320 A (MATSUSHITA ELECTRIC INDUSTRIAL CO. LTD.) 15 April 1998 (1998-04-15) * the whole document *	1,2,7	H04N5/445
A	US 5 361 173 A (ISHII T. ET AL) 1 November 1994 (1994-11-01) * column 29, line 58 - column 31, line 68 *	1,2,7	
A	EP 0 892 554 A (MATSUSHITA ELECTRIC INDUSTRIAL CO LTD) 20 January 1999 (1999-01-20) * column 7, line 43 - column 8, line 17 * * column 69, line 46 - column 70, line 5 *	1,2,7	
A	US 4 706 121 A (YOUNG P.) 10 November 1987 (1987-11-10) * column 19, line 49 - line 66 *	1,2,7	
A	US 5 686 954 A (YOSHINOBU H. ET AL) 11 November 1997 (1997-11-11) * column 25, line 45 - column 27, line 39 *	1,2,7	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	US 5 826 168 A (INOUE H. ET AL) 20 October 1998 (1998-10-20) * the whole document *	1,2,7	H04N
A	US 5 774 186 A (BRODSKY M. ET AL) 30 June 1998 (1998-06-30) * the whole document *	1,2,7	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>23 February 2000</b>	Examiner <b>Verschelden, J</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO Form 1503 (03.98) (P04001)



**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 0857

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-02-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 836320 A	15-04-1998	JP 10174037 A	26-06-1998
US 5361173 A	01-11-1994	JP 3215891 A	20-09-1991
		JP 2805102 B	30-09-1998
		JP 3286444 A	17-12-1991
		DE 69122632 D	21-11-1996
		DE 69122632 T	13-03-1997
		EP 0439290 A	31-07-1991
EP 892554 A	20-01-1999	JP 11008808 A	12-01-1999
		JP 11055637 A	26-02-1999
		JP 11164224 A	18-06-1999
		JP 11205706 A	30-07-1999
		CN 1216428 A	12-05-1999
		JP 11075128 A	16-03-1999
US 4706121 A	10-11-1987	NONE	
US 5686954 A	11-11-1997	JP 8102922 A	16-04-1996
		CN 1130843 A	11-09-1996
		EP 0705036 A	03-04-1996
US 5826168 A	20-10-1998	JP 8079685 A	22-03-1996
		JP 8116515 A	07-05-1996
		CN 1129879 A	28-08-1996
		EP 0700206 A	06-03-1996
		US 5729280 A	17-03-1998
		US 5884141 A	16-03-1999
		US 5990881 A	23-11-1999
US 5774186 A	30-06-1998	JP 9233415 A	05-09-1997

EPO FORM P0058

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82